

ProTag Optima

Best Value, Fully Portable Data Logging and Tag Printing System



- Optima II System - Seaward PrimeTest 300 & Optima Printer
- Appliance & RCD Testing, Tag Printing and Data Logging of Inspections
- No Interface Cables - Wireless Connections Using Bluetooth Technology
- Light Weight - Complete System Weighs Around 2kg
- PATGuard PRO Asset Management Software

The ProTag™ Optima II System is Australia's best value appliance and RCD testing, tag printing and record keeping system.

The Optima System is a next generation solution that combines the latest handheld instrument and wireless communications technology to provide the ultimate in portability and eliminating the need for connection cables between the appliance tester, tag printer and scanner.

Testing & Tagging System

The ProTag™ Optima System comprises of the Seaward PrimeTest 300 appliance and RCD tester, ProTag Optima test tag printer and PATGuard PRO software.

The PrimeTest 300 carries out all of the tests required under AS/NZS3760 for appliances and leads, and carries out 30mA RCD tests.

Risk Assessments & Data Logging

The PrimeTest 300 also operates as a handheld data logging device by recording any type of test,

inspection or risk assessment with user defined inspection routines and an in-built library of measurement and engineering units for recording actual results. This eliminates the need for a PDA or laptop for recording the results of various inspections and risk assessments, from microwave oven leakage and emergency lighting through to thermal surveys of switchboards.

Battery Powered & 2kg Weight

Each component in the Optima System is battery powered and together the system weighs around 2kg. Whether testing construction sites, workshops or factories, the Optima System's portability provides the most flexible testing and tagging solution, guaranteeing greater efficiency, huge time savings and a lower cost per test.

No Interface Cables

The Optima test tag printer connects to the Primetest 300 via wireless Bluetooth technology, eliminating connection cables and providing users with complete mobility.



PrimeTest 300 ...Your Complete Solution

The Primetest 300 is a top of the line tester, loaded with the latest technology making testing faster and more efficient. Bluetooth technology means it communicates with the Optima II printer without cables.

Seaward	Features
	PrimeTest 300
Display	Bright LCD
Indication	Pass/Fail, Reading
Operation	Alpha-numeric Keypad
Interface	Bluetooth/USB Adaptor
Leads	Earth Bond, IEC Lead
Carry Case	Deluxe Padded
Dimensions(LxWxH)	260 x 100 x 55mm
Weight	950g

Seaward	Tests Performed
	PrimeTest 300
Lead & Socket Polarity	Yes
Earth Continuity & Continuity	200mA, 1ohm
Insulation Resistance	500V DC, 1Mohm
Class I Leakage Current	5mA
Class II Leakage Current	1mA
MOV Devices Class I Leakage Current	5mA
MOV Devices Class II Leakage Current	1mA
Cord Extension Sets Leakage Current	1mA
RCD Test, 30mA RMS	<300ms
Power Source	6 x AA NIMH rechargeable batteries

Charger and rechargeable batteries included as standard.

Seaward	Results Displayed
	PrimeTest 300
Polarity	Pass/Fail
Earth Continuity	Pass/Fail/Value
Insulation Resistance	Pass/Fail/Value
Class I & II Leakage	Pass/Fail/Value
RCD Test	Pass/Fail/Value
User Defined Tests/Routines	Pass/Fail/Values

ProTag Optima - Options

ProTag Optima II	Features
	ProTag Optima II
BCS-OPT	Bar Code Scanner
PAC-3P	3 Phase Earth & Leakage Adaptor
TPI Series	3 Phase Insulation Test Adaptors
OPT-CASE	Hard Type Transit Case



Emona Instruments Pty Ltd
email: testinst@emona.com.au
web: www.protag.com.au www.emona.com.au

NSW – Sales & Service
78 Parramatta Road
Camperdown N.S.W 2050
Tel (02) 9519 3933
Fax (02) 9550 1378

VIC – Sales
1206 Toorak Road
Camberwell VIC 3124
Tel (03) 9889 0427
Fax (03) 9889 0715

QLD – Sales
1019 Ipswich Rd
Moorooka QLD 4105
Tel (07) 3392 7170
Fax (07) 3848 9046

WA – Sales
63 Shepparton Road
Victoria Park WA 6100
Tel (08) 9361 4200
Fax (08) 9361 4300

SA, TAS & NT – Sales
3/26 The Parade West
Kent Town SA 5067
Tel (08) 8363 5733
Fax (08) 8363 5799

OPTIMA ...Test Tag Printer

No more handwriting test tags! No more connection cables! Print durable and permanent synthetic test tags within seconds from the Primetest 300 via Bluetooth.

OPTIMA II Printer	Features
	OPTIMA II Printer
Print Method	Thermal Direct
Print Resolution	203dpi
Memory	2MB Flash RAM
Interfaces	Bluetooth, RS232
Dimensions	76.2 x 152.4 x 190.5mm
Weight	907g
Power Source	Lithium-ion rechargeable battery
Enclosure	Rubber-infused plastic over-mold. Damage resistant to multiple drops of up to 1.5m

Test Tag Specifications	
	OPTIMA Tags
Tags	Continuous Roll
Size	100mm x 50mm
Material	Durable Synthetic
Adhesive	Permanent
Tag Colours	Yellow, White, Green, Orange, Blue, Red
Tags Per Roll	250

PATGuard PRO - Software

Professional level reporting and asset history software. Automatically generates customer and test history database guaranteeing accountability and data reliability.

PATGuard PRO	
	PATGuard PRO
	Automatic record generation
	Icon style display easy to navigate
	Drag & Drop asset management
	Network enabled
	Automatic asset re-location
	Full test history per asset maintained
	Asset tracking and asset management

For more information visit our website

www.protag.com.au SEAWARD ELECTRONIC LTD.